


In re Patent Application of:  
**ROSSIN ET AL.**  
Serial No. 09/518, 421  
Filed: MARCH 03, 2000

In the Claims:

Please amend the claims as follows:



1. (Currently Amended) A light source, comprising:

a semiconductor laser including a laterally confining optical waveguide having a reflecting first end and a second end, the optical waveguide having a first portion of a first width extending a first distance from the first end and a second portion of a second width, less than five microns, wider than said first width and extending a second distance from the second end, and a third portion extending from said first portion to said second portion and having a width that tapers from said second first width of said second first portion to said first ~~second~~ width of said first ~~second~~ portion; and

wherein the first portion filters lateral optical modes higher than a fundamental lateral optical mode, and an output is emitted from the second end of the optical waveguide, such that a far field beam profile of said output emitted from the second end of the optical waveguide has a peak at  $0^\circ$ , and a respective slope of said far field beam profile on either side of said peak has a polarity that remains constant with increase in divergence angle.

2. (original) A light source as recited in claim 1, further comprising an optical fiber having an input end, the optical fiber including a wavelength-selective reflector to provide

In re Patent Application of:

**ROSSIN ET AL.**

Serial No. 09/518, 421

Filed: MARCH 03, 2000

---

reflectance at a wavelength of light amplified in the semiconductor laser, and a light coupling system disposed to optically couple light from the second end of the optical waveguide into the input end of the optical fiber.

3. (original) A light source as recited in claim 2, wherein the wavelength-selective reflector is a Bragg fiber grating disposed within the optical fiber.

4. (original) A light source as recited in claim 2, wherein a reflectance value of the wavelength-selective reflector and a separation distance between the second end of the optical waveguide and the wavelength-selective reflector are selected to induce coherence collapse in light output from the laser.

5. (original) A light source as recited in claim 4, wherein a separation distance between the first and second ends exceeds 1 mm.

6. (original) A light source as recited in claim 4, wherein the reflectance value of the wavelength-selective reflector is less than 10%.

7. (original) A light source as recited in claim 6, wherein the semiconductor laser has a gain spectrum having a peak gain wavelength, the peak gain wavelength being substantially equal to a peak reflectance wavelength of the wavelength-selective

In re Patent Application of: .

**ROSSIN ET AL.**

Serial No. 09/518, 421

Filed: MARCH 03, 2000

---

reflector at a semiconductor laser temperature between 0 °C and 50 °C.

8. (original) A light source as recited in claim 4, wherein a separation distance between the second end of the optical waveguide and the wavelength-selective reflector is in the range 0.5 m to 2 m.

9. (original) A light source as recited in claim 2, wherein the wavelength-selective reflector reflects light within a selected reflection bandwidth, and light emitted by the semiconductor laser has a spectral bandwidth approximately equal to the reflection bandwidth.

10. (original) A light source as recited in claim 1, wherein the second end of the optical waveguide is provided with an anti-reflection coating.

11. (original) A light source as recited in claim 1, wherein each of the first and second waveguide portions have a substantially uniform respective width.

12. (original) A light source as recited in claim 1, wherein the tapered portion of the optical waveguide has a length of at least 100  $\mu\text{m}$ .

13. (original) A light source as recited in claim 1, wherein

In re Patent Application of:

**ROSSIN ET AL.**

Serial No. 09/518, 421

Filed: MARCH 03, 2000

---

the laterally confining optical waveguide is formed in a planar structure.

14. (original) A light source as recited in claim 1, wherein an optical mode of the laterally confining optical waveguide is transversely asymmetric.

15. (original) A light source as recited in claim 1, further comprising a power supply coupled to supply electrical current to the laser.

16. (original) A light source as recited in claim 1, further comprising a temperature controller coupled to maintain the laser at a selected operating temperature.

17. (Amended) A fiber optic system, comprising:

a communications fiber having a first end and a second end, the communications fiber including an excitable fiber medium; and

a pump laser coupled to supply pump light to the excitable fiber medium, the pump laser including a laterally confining optical waveguide having a first end of a first width provided with a high reflector, and a second end of a second width, the optical waveguide having a first portion of said first width and extending a first distance from the first end and a second portion of said second width, less than five microns, and wider than said first width, and extending a second distance from the

In re Patent Application of:

**ROSSIN ET AL.**

Serial No. 09/518, 421

Filed: **MARCH 03, 2000**

---

second end, and a third portion extending from said first portion to said second portion and having a width that tapers from said second first width of said second first portion to said first second width of said first second portion; and

wherein, the first portion filters out lateral optical modes higher than a fundamental lateral optical mode, and an output is emitted from the second end of the optical waveguide, such that a far field beam profile of said output emitted from the second end of the optical waveguide has a peak at 0°, and a respective slope of said far field beam profile on either side of said peak has a polarity that remains constant with increase in divergence angle.

18. (original) A system as recited in claim 17, further comprising a first optical fiber coupled to the communications fiber, and having an input end, the first optical fiber including a wavelength selective reflector providing reflectance at a wavelength of light amplified in the pump laser, and a light focusing system disposed to optically couple light from the second end of the optical waveguide into the input end of the first optical fiber.

19. (original) A system as recited in claim 18, wherein the wavelength selective reflector includes a fiber Bragg grating disposed within the first optical fiber.

20. (original) A system as recited in claim 18, wherein the

In re Patent Application of:

**ROSSIN ET AL.**

Serial No. **09/518, 421**

Filed: **MARCH 03, 2000**

---

wavelength selective reflector includes a second optical fiber optically coupled to the first optical fiber between the pump laser and the communications fiber, a fiber Bragg grating being disposed within the second optical fiber.

21. (original) A system as recited in claim 18, wherein a reflectance value of the wavelength selective reflector and a separation distance between the second end of the optical waveguide and the wavelength selective reflector are selected to induce coherence collapse in light output from the laser.

22. (original) A system as recited in claim 17, wherein the excitable fiber medium is a rare-earth doped fiber amplifier.

23. (original) A system as recited in claim 17, wherein the excitable fiber medium is a rare-earth doped fiber laser.

24. (original) A system as recited in claim 17, wherein light output from the pump laser induces Raman gain in the excitable fiber medium.

25. (original) A system as recited in claim 24, wherein the excitable fiber medium is a fiber Raman amplifier.

26. (original) A system as recited in claim 24, wherein the excitable fiber medium is a fiber Raman resonator.

In re Patent Application of:  
**ROSSIN ET AL.**  
Serial No. **09/518, 421**  
Filed: **MARCH 03, 2000**

---

27. (original) A system as recited in claim 17, further comprising an optical transmitter coupled at a first end of the communications fiber to transmit optical signals along the communications fiber.

28. (original) A system as recited in claim 17, further comprising an optical receiver coupled to receive optical signals at a second end of the communications fiber.

29. (original) A system as recited in claim 17, further comprising a controller coupled to the pump laser to control operation of the pump laser.

30. (original) A system as recited in claim 29, wherein the controller includes a power supply coupled to the pump laser to provide current to the pump laser.

31. (original) A system as recited in claim 29, wherein the controller includes a temperature controller coupled to the pump laser to control a temperature of the pump laser.

32. (previously added) The light source according to claim 1, wherein said first width is on the order of 2.3 microns and said second width is on the order of 4.3 microns.

In re Patent Application of:

**ROSSIN ET AL.**

Serial No. **09/518, 421**

Filed: **MARCH 03, 2000**

---

33. (previously added) The system according to claim 17, wherein said first width is on the order of 2.3 microns and said second width is on the order of 4.3 microns.